



MST-800VD Morooka Rubber Track Carriers

Performance	
Max. Carrying Capacity	9460 lbs.
Travel Speed - 1st Gear	5.1 mph
Travel Speed - 2nd Gear	7.5 mph
Gradeability (unloaded)	30 degrees
Turning Radius	7' 9"
Ground Pressure	2.3 psi
Ground Pressure (loaded)	3.8 psi



Engine
Make: Mitsubishi
Model: 4D34-TE2
4 cylinders
Displacement: 3.9 liters
115 hp @ 2,200 rpm
Fuel tank capacity: 27.7 gal.

Dimensions	
Full Length	14' 6"
Full Width	7' 7"
Wheel Base	10' 3"
Min. Ground Clearance	18"
Front Overhang	2' 3"
Gauge	5' 7"
Track Width	23"
Track Length	26' 3"
Full Height	7' 10"
Height of Dump Bed	3' 10"
Height of Dump Side	1' 2"
Length of Dump Bed	8' 6"
Width of Dump Bed	6' 5"
Dumping Angle	58 deg.
Machine Weight	13,448 lbs.

Other Models; Quick Spec. Chart

Model	Weight	Load	Horsepower
MST300VD/R	5,000 lbs.	5,000 lbs.	46 hp
MST600VD	8,800 lbs.	7,260 lbs.	76 hp
MST1500VD	20,282 lbs.	13,892 lbs.	204 hp
MST2200VD	29,762 lbs.	22,050 lbs.	250 hp

For more information contact: Equipment Direct, Inc, www.eqdirect.com, sales@eqdirect.com